

# EsterTec

synthetic esters




**ZSCHIMMER & SCHWARZ**

Chemistry tailor-made

## A New Synthetic Ester Product Technology Is Now Available

EsterTec vicinal secondary polyol (VSP) esters offer exceptional performance based on their innovative structure achieved via a unique production process. Utilizing standard raw materials that are globally accessible, these esters ensure high stability through vicinal ester molecular positioning. Steric hindrance enhances oxidative stability, while secondary alcohols on adjacent carbons significantly improve hydrolytic stability. Experience the next level of synthetic lubricant performance by formulating with EsterTec VSP diesters.



## EsterTec VSP: Best-in-Class Synthetic Lubricant Base Stock Designed for Outstanding Performance Value and Reliability

With a broad viscosity range and operating temperature window, EsterTec affords superior control of friction and reduces wear, ensuring the stability and long life of high-performance lubricants. This advanced component is miscible with PAO and petroleum base stocks, as well as compatible with standard elastomers and seals. EsterTec excels in heat transfer, features excellent dielectric properties, and exhibits high flash and fire points for enhanced safety in both lubricant and electrical insulating fluid applications. Environmentally friendly, with a high biogenic content, EsterTec is readily biodegradable and USDA BioPreferred, making it a top choice for those seeking efficiency and sustainability on their ESG scorecard.

## Benefit From All the Performance Advantages of a Diester or Polyol Ester, Plus Exceptional Benefits That Set This Technology Apart:

- **Natural Energy Efficiency:** Leverage their low density, high viscosity index (VI), and superior lubricity, for enhanced energy savings.
  - **Best-in-Class Stability:** Enjoy an unparalleled combination of oxidative, thermal, and hydrolytic stability, optimized for extended product life and consistent performance in applications that experience high temperatures or water ingress.
  - **Optimal Heat Transfer and Dielectric Properties:** Achieve excellent thermal management and dielectric insulation, which can be leveraged in EV cooling applications.
  - **High Biogenic Content:** Choose an environmentally friendly option that has a higher biogenic content compared to many synthetic diester or polyol esters.
  - **Cost-Effective:** Save more due to lower cost per unit volume. Molecular design leads to significant lower density compared to standard esters.
- EsterTec VSP sets the standard for a new class of polyol ester that delivers a blend of high performance, efficiency, sustainability and outstanding value.
- **Wide Temperature Operating Range:** Reliable operation from  $-60^{\circ}\text{C}$  to  $200^{\circ}\text{C}$ , enhancing low temperature viscometrics and high temperature stability.
  - **Enhanced Friction and Wear Control:** Improved protection for components, reducing maintenance costs and downtime.
  - **Energy Efficiency:** Lower energy consumption, translating to significant savings over time.
  - **Environmentally Friendly:** A sustainable choice for next-generation lubricant formulations.

EsterTec excels in numerous fields of application, delivering exceptional performance, value, and reliability across various industries, including:



Metalworking fluids



Hydraulic fluids



Engine oils



Compressor fluids



Bearing lubricants



EALs for environmentally sensitive applications



H1 food-grade lubricants



Greases



Transmission fluids



Gear oils



Drilling mud lubricants



Transformer oils



Multifunctional dielectric/coolant/lubricants



Oven chain oils

## Superior Performance

EsterTec VSP esters can be used to optimize premium synthetic lubricant formulations for use in high-performance applications. Technical and economic benefits include:

### Oxidative Stability

Resists degradation at high temperatures, minimizing deposits and sludge formulation; noncorrosive to iron, aluminum, or copper.

### Hydrolytic Stability

Remains stable and effective even in the presence of moisture from condensation or contamination; achieves effective long-life performance in aqueous metalworking fluids.

### Friction/Wear Reduction

Minimizes energy losses due to friction, improving energy efficiency.

### Energy Efficiency

Low density that leads to decreased pumping energy requirements and reduced weight in mobile applications; helps conserve energy usage compared to standard lubricants.

### Cost-Effectiveness

Affords favorable total cost of ownership through its efficiency and performance results; lower density = lower shipping costs.

### Eco-Friendliness

High biogenic content, readily biodegradable, and low aquatic toxicity, making EsterTec VSP esters the preferred choice for EAL formulations.

# PERFORMANCE DATA

EsterTec VSP: Advanced Synthetic Lubricant Technology That Delivers Across Every Performance Metric

## EsterTec VSP Products – ISO 15 to ISO 32


Product Name	ESTERTEC 2N-1416	ESTERTEC 2LN-1418	ESTERTEC 2G-1432
KV100, cSt	3.6	4.1	6.8
KV40, cSt	16	18	33
Viscosity Index	110	125	180
Pour Point, °C	-60	-40	-42
Density	0.895	0.893	0.890
Noack volatility, %	9	7	1
Biogenic Content, %	64	65	74
Oxidative Stability	✓	✓	✓
Hydrolytic Stability	✓	✓	✓
Friction/Wear Reduction	✓	✓	✓
Energy-Efficiency Advantage	✓	✓	✓
Cost/Performance Advantage	✓	✓	✓



EsterTec delivers performance that is equal to or better than standard POE in the following areas:

- Pour Point
- Flash Point
- Foam Tendency
- Demulsibility
- Copper Corrosion
- Oxidative Stability
- Thermal Stability
- Specific Heat
- Thermal Conductivity
- Odor
- Color
- Clarity
- Miscibility with PAO
- Compatibility with Elastomers

## EsterTec Comparison Radar Chart



### EsterTec VSP: Cutting-Edge Synthetic Ester Lubricant Technology

EsterTec VSP esters are the latest advancement in synthetic ester molecular design, meticulously crafted to deliver versatile and reliable functionality. Through its innovative molecular structure and production process, this synthetic lubricant component offers:

**Superior Stability:** Exceptional resistance to oxidation, thermal breakdown, and hydrolysis, for extended service life.

**Excellent Control of Friction and Wear:** A unique molecular design that enables a balance of polar attraction to metal interfaces and surface packing under EHL conditions that reduce the coefficient of friction.

**Broad Operating Temperature Range:** Lubricants formulated with VSP esters for cold temperature applications exhibit low dynamic viscosity and excellent pour point, ensuring reliable performance in extreme conditions. For high-temperature applications, VSP esters offer low volatility and a high flash point, enhancing product durability and safety. The excellent viscometric properties of EsterTec VSP contribute to improved energy efficiency, making them the ideal solution for demanding industrial, automotive, and dielectric applications.

# EsterTec

synthetic esters



## ZSCHIMMER & SCHWARZ

Chemistry tailor-made

### ▶ AMERICAS

#### **Zschimmer & Schwarz Inc.**

70 GA Highway 22 W  
Milledgeville, GA 31061, USA  
T +1 478 454 1942  
lubricants@zschimmer-schwarz.com  
zslubes.com

#### **Zschimmer & Schwarz do Brasil Ltda.**

Estrada Geral Morro do Paula 546  
Distrito Industrial – Bairro São Borja  
93032-530 São Leopoldo, BR  
T +55 51 3566 1666  
zsb@zschimmer-schwarz.com.br  
zslubes.com

### ▶ EUROPE

#### **Zschimmer & Schwarz Italiana S.p.A.**

Via Angelo Ariotto, 1/C  
13038 Tricerro (VC), IT  
T +39 0161 808 111  
info.zsi@zschimmer-schwarz.com  
zslubes.com

#### **Zschimmer & Schwarz España S.p.A.**

Carretera CV-20  
km 3,200, Apdo. 118  
Vila-Real (Castellón) 12540, ES  
T + 34 964 62 63 65  
info.zse@zschimmer-schwarz.com  
zslubes.com

#### **Zschimmer & Schwarz GmbH & Co KG**

Max-Schwarz-Straße 3-5  
56112 Lahnstein, DE  
T +49 2621 12-0  
info@zschimmer-schwarz.com  
zschimmer-schwarz.com

### ▶ ASIA

#### **Zschimmer & Schwarz Chemical (China) Co., Ltd.**

No. 16, Kaiyuan Road  
Datang Industrial Park  
Sanshui, 528143 Foshan, Guangdong, CNT  
+86 757 87 27 06 01  
zsc@zschimmer-schwarz.cn  
zschimmer-schwarz.com

